

## Rain Bird® 952 Series

### Full / Part Circle Golf Rotors

#### Specifications

##### Radius:

- 70' - 101' (21.3m - 31.8m)

##### Flow Rate:

- 19.7 to 54.5 gpm (1.24 to 3.44 l/s)  
(4.43 to 12.38 m<sup>3</sup>/h)

##### Arc:

- Full-circle 360°, Adjustable 30° to 345°

##### Models:

- E: Electric
- IC: Integrated Control
- SAM: Stopmatic

##### Maximum Inlet Pressure:

- Models E and IC: 150 psi (10.3 bars)
- Model SAM: 100 psi (6.9 bars)

##### Pressure Regulation Range:

- Models E, IC: 60 to 100 psi (4.1 to 6.9 bars)

##### Factory Pressure Settings:

- Models E and IC available in 70 and 80 psi (4.8 and 5.5 bars)

##### Dimensions:

- Body Height: 13.4" (34.0 cm)
- Pop-Up Height to Mid-Nozzle: 2.6" (6.6 cm)
- Top Diameter: 7.0" (17.8 cm)

##### Nozzle Trajectory:

- Standard: 25°
- Low Angle: 17°

##### Inlet Threads:

- Models E, IC, SAM: 1.5 (38mm) ACME female thread

##### Holdback:

- SAM: 17' (5.2m) elevation

##### Rotation Time:

- 180° in ≤ 100 seconds; 80 seconds nominally

##### Maximum Stream Height:

- Standard: 22' (6.7m)
- Low Angle: 12' (3.7m)

##### Solenoid:

- 24 VAC solenoid power requirement: 0.41 amp inrush current (9.8 VA); 60 Hz: 0.25 amp holding current (6.0 VA); 50 Hz: 0.32 amp holding current (7.7 VA)

##### Surge Resistance:

- 25kV standard on electric models

##### Top-Serviceable Rock Screen™ and Replaceable Valve Seat:

- All 952 models

##### Special Features:

- Self-Adjusting Stator
- Standard 952 ships with rear nozzle plug



#### RAPID-ADJUST TECHNOLOGY

Make easy arc adjustments with the turn of a screw. MemoryArc® feature retains two part-circle arc settings, so you can shift between full- and part-circle operation in seconds.



**Step 1:** Set primary rotor arc.



**Step 2:** Turn the Full/Part Adjustment Screw for full-circle operation.



**Step 3:** Turn the rotor to either Arc A or Arc B setting, then set to part-circle. No need to reset the arc when changing between full- and part-circle settings.



#### How To Specify

A	952	XX	XX	XX
Thread Type ACME	Model 952	Body/ Valve E IC SAM	Pressure Regulator 70 (4.8) 80 (5.5)	Nozzle 44, 48, 52, 56, 60, 64

##### Descriptive text for understanding only!

Model number would look like A952IC8052 when a customer orders the IC version with a #52 nozzle at a case pressure of 80 PSI

(continued)



## U.S. Performance Data

Dual Spreader™ Nozzles													
	Base Pressure (psi)	#44 - Blue		#48 - Yellow		#52 - Orange		#56 - Green		#60 - Black		#64 - Red	
		Radius (ft)	Flow (gpm)	Radius (ft)	Flow (gpm)	Radius (ft)	Flow (gpm)	Radius (ft)	Flow (gpm)	Radius (ft)	Flow (gpm)	Radius (ft)	Flow (gpm)
Standard	60	70	19.7	76	27.1	79	31.5	81	35.3	83	38.8	85	42.0
	70	71	21.3	78	29.7	81	34.0	84	38.2	86	42.1	89	47.1
	80	73	22.8	79	31.6	83	36.3	87	41.0	88	44.9	93	48.7
	90	73	23.8	82	33.3	85	38.4	90	42.8	91	47.6	98	51.7
	100	74	25.0	82	35.1	88	40.6	92	45.5	94	49.1	101	54.5
Low Angle	60	70	19.7	77	27.7	78	31.8	82	35.9	81	39.4	-	-
	70	74	21.1	80	30.0	83	34.2	87	38.7	86	42.6	-	-
	80	76	22.9	82	31.5	86	36.6	89	40.9	89	45.6	-	-
	90	77	24.1	84	33.5	87	38.7	90	43.4	92	48.1	-	-
	100	79	25.4	86	35.4	89	40.8	94	46.0	96	51.0	-	-

## Metric Performance Data

Dual Spreader™ Nozzles																			
	Base Pressure (bar)	#44 - Blue			#48 - Yellow			#52 - Orange			#56 - Green			#60 - Black			#64 - Red		
		Radius (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	Flow (m³/h)	Flow (l/s)	Radius (m)	Flow (m³/h)	Flow (l/s)
Standard	4.1	21.3	4.5	1.24	23.2	6.2	1.71	24.1	7.2	1.99	24.7	8.0	2.23	25.3	8.8	2.45	25.9	9.5	2.65
	4.8	21.6	4.8	1.34	23.8	6.7	1.87	24.7	7.7	2.15	25.6	8.7	2.41	26.2	9.6	2.66	27.1	10.7	2.97
	5.5	22.3	5.2	1.44	24.1	7.2	1.99	25.3	8.2	2.29	26.5	9.3	2.59	26.8	10.2	2.83	28.3	11.1	3.07
	6.2	22.3	5.4	1.50	25.0	7.6	2.10	25.9	8.7	2.42	27.4	9.7	2.70	27.7	10.8	3.00	29.9	11.7	3.26
	6.9	22.6	5.7	1.58	25.0	8.0	2.21	26.8	9.2	2.56	28.0	10.3	2.87	28.7	11.2	3.10	30.8	12.4	3.44
Low Angle	4.1	21.3	4.5	1.24	23.5	6.3	1.75	23.8	7.2	2.01	25.0	8.2	2.26	24.7	8.9	2.49	-	-	-
	4.8	22.6	4.8	1.33	24.4	6.8	1.89	25.3	7.8	2.16	26.5	8.8	2.44	26.2	9.7	2.69	-	-	-
	5.5	23.2	5.2	1.44	25.0	7.2	1.99	26.2	8.3	2.31	27.1	9.3	2.58	27.1	10.4	2.88	-	-	-
	6.2	23.5	5.5	1.52	25.6	7.6	2.11	26.5	8.8	2.44	27.4	9.9	2.74	28.0	10.9	3.03	-	-	-
	6.9	24.1	5.8	1.60	26.2	8.0	2.23	27.1	9.3	2.57	28.7	10.4	2.90	29.3	11.6	3.22	-	-	-

**Rain Bird Corporation**  
6991 E. Southpoint Road  
Tucson, AZ 85756  
Phone: (520) 741-6100  
Fax: (520) 741-6522

**Rain Bird Corporation**  
970 West Sierra Madre Avenue  
Azusa, CA 91702  
Phone: (626) 812-3400  
Fax: (626) 812-3411

**Rain Bird International, Inc.**  
1000 West Sierra Madre Ave.  
Azusa, CA 91702  
Phone: (626) 963-9311  
Fax: (626) 852-7343

**Rain Bird Technical Services**  
(800) RAINBIRD (1-800-724-6247)  
(U.S. and Canada)

**Specification Hotline**  
800-458-3005 (U.S. and Canada)

The Intelligent Use of Water™  
[www.rainbird.com](http://www.rainbird.com)