



## STANDAARD MP ROTATOR NOZZLES - VERSTELBAAR

Te gebruiken met de Pro-Spray-serie sproeiers

### MP1000

Reikwijdte: 2,5 tot 4,5 m

● 90° tot 210°

● 210° tot 270°

● 360°

### MP2000

Reikwijdte: 4,0 tot 6,4 m

● 90° tot 210°

● 210° tot 270°

● 360°

### MP3000

Reikwijdte: 6,7 tot 9,1 m

● 90° tot 210°

● 210° tot 270°

● 360°

| Nozzle | Druk       | Reikwijdte<br>m | Water<br>verbruik l/uur | Reikwijdte<br>m | Water<br>verbruik l/uur | Reikwijdte<br>m | Water<br>verbruik l/uur |
|--------|------------|-----------------|-------------------------|-----------------|-------------------------|-----------------|-------------------------|
| 90°    | 2.1        | 3.7             | 38                      | 5.5             | 86                      | 8.2             | 173                     |
|        | 2.5        | 4.0             | 43                      | 5.8             | 91                      | 8.5             | 187                     |
|        | <b>2.8</b> | <b>4.1</b>      | <b>48</b>               | <b>6.1</b>      | <b>98</b>               | <b>9.1</b>      | <b>196</b>              |
|        | 3.0        | 4.3             | 52                      | 6.4             | 104                     | 9.1             | 205                     |
|        | 3.5        | 4.5             | 57                      | 6.4             | 107                     | 9.1             | 216                     |
|        | 3.8        | 4.5             | 61                      | 6.4             | 109                     | 9.1             | 230                     |
| 180°   | 2.1        | 3.7             | 77                      | 5.2             | 146                     | 8.2             | 359                     |
|        | 2.5        | 4.0             | 86                      | 5.5             | 161                     | 8.5             | 386                     |
|        | <b>2.8</b> | <b>4.1</b>      | <b>95</b>               | <b>5.8</b>      | <b>175</b>              | <b>9.1</b>      | <b>414</b>              |
|        | 3.0        | 4.3             | 100                     | 6.1             | 193                     | 9.1             | 439                     |
|        | 3.5        | 4.5             | 114                     | 6.4             | 207                     | 9.1             | 464                     |
|        | 3.8        | 4.5             | 116                     | 6.4             | 216                     | 9.1             | 484                     |
| 270°   | 2.1        | 3.7             | 109                     | 5.2             | 216                     | 8.2             | 539                     |
|        | 2.5        | 4.0             | 121                     | 5.5             | 234                     | 8.5             | 580                     |
|        | <b>2.8</b> | <b>4.1</b>      | <b>143</b>              | <b>5.8</b>      | <b>250</b>              | <b>9.1</b>      | <b>621</b>              |
|        | 3.0        | 4.3             | 152                     | 6.1             | 266                     | 9.1             | 657                     |
|        | 3.5        | 4.5             | 164                     | 6.4             | 280                     | 9.1             | 696                     |
|        | 3.8        | 4.5             | 170                     | 6.4             | 296                     | 9.1             | 732                     |
| 360°   | 2.1        | 3.7             | 157                     | 5.2             | 291                     | 8.2             | 716                     |
|        | 2.5        | 4.0             | 175                     | 5.5             | 311                     | 8.5             | 773                     |
|        | <b>2.8</b> | <b>4.1</b>      | <b>191</b>              | <b>5.8</b>      | <b>337</b>              | <b>9.1</b>      | <b>828</b>              |
|        | 3.0        | 4.3             | 200                     | 6.1             | 357                     | 9.1             | 878                     |
|        | 3.5        | 4.5             | 223                     | 6.4             | 382                     | 9.1             | 926                     |
|        | 3.8        | 4.5             | 230                     | 6.4             | 395                     | 9.1             | 971                     |

### MP3500

Reikwijdte: 9,4 tot 10,7 m

● 90° tot 210°

| Nozzle | Druk       | Reikwijdte<br>m | Water<br>verbruik l/uur |
|--------|------------|-----------------|-------------------------|
| 90°    | 2.1        | 10.4            | 257                     |
|        | 2.5        | 10.4            | 275                     |
|        | <b>2.8</b> | <b>10.7</b>     | <b>290</b>              |
|        | 3.0        | 10.7            | 313                     |
|        | 3.5        | 10.7            | 325                     |
|        | 3.8        | 10.7            | 341                     |
| 180°   | 2.1        | 10.4            | 509                     |
|        | 2.5        | 10.4            | 602                     |
|        | <b>2.8</b> | <b>10.7</b>     | <b>650</b>              |
|        | 3.0        | 10.7            | 704                     |
|        | 3.5        | 10.7            | 729                     |
|        | 3.8        | 10.7            | 745                     |
| 210°   | 2.1        | 10.4            | 645                     |
|        | 2.5        | 10.4            | 700                     |
|        | <b>2.8</b> | <b>10.7</b>     | <b>747</b>              |
|        | 3.0        | 10.7            | 804                     |
|        | 3.5        | 10.7            | 854                     |
|        | 3.8        | 10.7            | 895                     |

Optimaal aanbevolen druk: 2,8 bar. Bij een druk tot 2,1 bar, gebruik Pro-Spray PRS30. Bij een druk van 2,8 bar, gebruik Pro-Spray PRS40.

