



MP ROTATOR MP800 NOZZLES - VERSTELBAAR

Te gebruiken met de Pro-Spray-serie sproeiers

MP800SR

Reikwijdte: 1,8 tot 3,5 m

● 90° tot 210° ● 360°

MAX REIKWIJDTE				MIN REIKWIJDTE		
Nozzle	Druk	Reikwijdte m	Water verbruik l/uur	Reikwijdte m	Water verbruik l/uur	
90° 	2.1	2.6	37	1.8	29	
	2.5	2.9	43	2.1	33	
	2.8	3.1	52	2.4	37	
	3.0	3.4	57	2.4	41	
	3.5	3.5	61	2.7	43	
	3.8	3.5	64	3.0	46	
180° 	2.1	2.6	73	1.8	59	
	2.5	2.8	84	2.1	66	
	2.8	3.0	95	2.4	73	
	3.0	3.3	104	2.4	82	
	3.5	3.4	109	2.7	86	
	3.8	3.5	113	3.0	91	
210° 	2.1	2.6	84	1.8	69	
	2.5	2.8	100	2.1	77	
	2.8	3.0	111	2.4	85	
	3.0	3.2	121	2.4	95	
	3.5	3.4	127	2.7	101	
	3.8	3.5	132	3.0	106	
360° 	2.1	2.6	143	1.8	107	
	2.5	2.8	159	2.1	118	
	2.8	3.0	177	2.4	127	
	3.0	3.1	193	2.4	134	
	3.5	3.3	200	2.7	143	
	3.8	3.5	223	3.0	159	

MP815

Reikwijdte: 2,5 tot 4,9 m

● 90° tot 210° ● 210° tot 270° ● 360°

Nozzle	Druk	Reikwijdte m	Water verbruik l/uur
90° 	2.1	4.3	95
	2.5	4.5	104
	2.8	4.6	111
	3.1	4.8	118
	3.5	4.9	125
	3.8	4.9	132
180° 	2.1	4.0	170
	2.5	4.3	196
	2.8	4.5	211
	3.1	4.6	218
	3.5	4.8	241
	3.8	4.9	252
270° 	2.1	4.0	259
	2.5	4.3	281
	2.8	4.5	318
	3.1	4.6	334
	3.5	4.8	350
	3.8	4.9	365
360° 	2.1	4.0	345
	2.5	4.3	386
	2.8	4.5	425
	3.1	4.6	454
	3.5	4.8	484
	3.8	4.9	513

Optimaal aanbevolen druk: 2,8 bar. Bij een druk tot 2,1 bar, gebruik Pro-Spray PRS30. Bij een druk van 2,8 bar, gebruik Pro-Spray PRS40.

